

DESCRIPTION


- ELECTRONIC BALLAST
- ELECTRONIC TRANSFORMER
- SWITCH MODE POWER SUPPLY

FEATURES:

- LOW THERMAL RESISTANCE
- HIGH INPUT RESISTANCE
- FAST SWITCHING
- ROHS COMPLIANT

MAXIMUM RATINGS (T_c=25°C)

PARAMETER	SYMBOL	VALUE	UNIT
Drain-source Voltage	V _{DS}	650	V
gate-source Voltage	V _{GS}	±30	V
Continuous Drain Current (T _C =25°C)	I _D	4	A
Drain Current-Pulsed	I _{DM}	16	A
Total Dissipation	PD	30	W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55-150	°C
Single Pulse Avalanche Energy	E _{AS}	130	mJ

MECHANICAL

ELECTRONIC CHARACTERISTICS (T_c=25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	MAX	UNIT
Drain-source Breakdown Voltage	B _V D _{SS}	V _{GS} =0V, I _D =250 μA	650		V
Gate Threshold Voltage	V _{GS} (TH)	V _{GS} =V _{DS} , I _D =250 μA	2	4	V
Drain-source Leakage Current	I _{DSS}	V _{DS} =650V, V _{GS} =0V		25	μA
Drain-Source Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =4A		1.4	V
Gate-body Leakage Current (V _{DS} = 0)	I _{GSS}	V _{GS} =±30V		±100	nA
Forward Transconductance	g _{fs}	V _{ds} =10V I _d =2.0A	0.5		S
Static Drain-source On Resistance	R _{DS} (ON)	V _{GS} =10V, I _D =2.0A		2.8	Ω
Thermal Resistance Junction-case	R _{thJ-c}			3	°C/W

■ DYNAMIC CHARACTERISTICS (T_c=25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1.0MHz	-	610	-	pF
output Capacitance	C _{oss}		-	62	85	pF
Reverse Transfer Capacitance	C _{rss}		-	7	10	pF

■ SWITCHING CHARACTERISTICS (T_c=25°C)







CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Turn-On Delay Time	t _{d(on)}	V _{DD} =300V, I _D =4.0A, R _G =25Ω	-	20	40	ns
Turn-On Rise Time	t _r		-	30	70	ns
Turn-Off Delay Time	t _{d(off)}		-	25	100	ns
Turn-Off Rise Time	t _f		-	35	85	ns
Total Gate Charge	Q _g	V _{DS} =520V, I _D =4.0A, V _{GS} =10V	-	13.7	-	nC
Gate-Source Charge	Q _{gs}		-	2.9	-	nC
Gate-Drain Charge	Q _{gd}		-	4.6	-	nC

■ DRAIN-SOURCE DIODE MAXIMUM RATINGS AND CHARACTERISTICS (T_c=25°C)

CHARACTERISTICS	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Max. Diode Forward Current	I _S		-	-	4	A
Max. Pulsed Forward Current	I _{SM}		-	-	16	A
Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =4.0A	-	-	1.4	V
Reverse Recovery Time	t _{rr}	V _{GS} =0V, I _S =4.0A, dI _F /dt=100A/μs	-	390	-	ns
Reverse Recovery Charge	Q _{rr}		-	1.5	-	μC




CHARACTERISTICS CURVE







CHARACTERISTICS CURVE



Gate Charge Waveform



Source-Drain Diode Forward Voltage



Breakdown Voltage Vs Junction Temperature

TO-220F MECHANICAL DATA

UNIT: mm

SYMBOL	MIN	NOM	MAX	SYMBOL	MIN	NOM	MAX
A	4.5		4.9	E1	6.5	7	7.5
A1	2.3		2.9	e	2.44	2.54	2.64
b	0.65		0.9	L	12.5		14.3
b1	1.1		1.7	L1	9.45		10.05
b2	1.2		1.4	L2	15		16
c	0.35		0.65	L3	3.2		4.4
D	14.5		16.5	ΦP	3		3.3
D1	6.1		6.9	Q	2.5		2.9
E	9.6		10.3				

